



PRODUCT SPECIFICATION / DATA SHEET

PRODUCT CODE: XT-7655	CURRENT REVISION:	8/31/2011
CLASIFICATION: <u>Industrial Grade Medical Felt</u>	REPLACES REVISION:	3/31/2008
DESCRIPTION: PTFE Needle Punch Felt - HD Roll Goods Unsupported -white in color	ORIGINAL DATE:	9/21/2004
	Raw Material:	100% PTFE
PACKAGING: Rolls wound on 3" cardboard cores plastic wrapped/ in box and/or on pallet	Fiber Specification:	A-088 Rev. A/LD
	Dated:	8/22/2005

PHYSICAL PROPERTIES

THICKNESS			.075"		
(ASTM D5729)			+/- .015"		

Custom thickness available as MTO

WEIGHT (osy)			28-40		
(ASTM D3776)					

Standard Width (in)			60"	23"	
Available (23" - 72")			+ 2"/-0"		

ROLL LENGTH (yds)			5 - 30		
-------------------	--	--	--------	--	--

MODIFIED BURST (psi)			300		
(ASTM D3786)			min		

TENSILE STRENGTH (psi)			400		
(ASTM D5034)			min		

ELONGATION			100%		
(ASTM D5035)					

POROSITY (cfm)			12-25		
(ASTM D737)					

COLOR & APEARANCE	White and mostly free from imbedded foreign matter, stains, grease, etc.				
-------------------	--	--	--	--	--

This information is provided solely as a specification for the physical properties of the products listed above. H&H does not claim or guarantee in any way these materials are fit for use in any particular application. Determining fitness for use is the sole responsibility of the user.